

TSL Mobile BT Printer



The **TSL Mobile BT Printer** is a small, lightweight mobile receipt printer that brings user convenience and functionality to any mobile receipt printing applications such as:

- Mobile POS/ Retail.
- Hospitality.
- Deliveries.
- Onboard Transportation.
- Field Repairs/ Installation.
- Warehouse/ Logistics.
- Utility billing/ Meter Reading.



Handheld size



Damage-resistance material
Rubber over-molding

Total Solutions
We know IT!

Level 3, Ameer Arcade, Westlands,
Tel: 254 20 3749056/7, 3747007
Fax: 254 20 3749058
E-mail: info@totalsolutions.co.ke
Website: www.totalsolutions.co.ke

Main Features For TSL MOBILE BT PRINTER :

Rugged Design & Small Size: Uniquely designed for harsh outdoor environments and handheld size the TSL MOBILE BT PRINTER is ideal for printing delivery receipts and invoices on the go.

OPTIONS

CRADLE: This optional battery cradle allows users to charge their spare battery while the printer is in use. Charge each Lithium-ion battery in approximately 2.5 hours.



QUAD CHARGER: You can charge upto 4 batteries at a time and never run out of batteries.



SPARE BATTERY: With a spare Lithium-ion battery you always be assured that TSL MOBILE BT Printer will be ready for you on the road.



CIGARETTE LIGHTER CHARGER: Is easily charged using the cigar lighter charger on the vehicle for road warriors.



LEATHER CASE: Equip your mobile protection in tough outdoor usage and to keep hands free.



SERIAL/USB INTERFACE CABLE: For users who prefer to use the mobile printer with interface cable, optional serial/USB cable is available.



FEATURES & SPECIFICATIONS

- Rugged design and small size.
- Damage resistance to multiple drops of up to 1.2 meters.
- Faster printing speeds-up to 80mm/sec.
- Long lasting Lithium-ion battery (7.4V, 1200mAh).
- Operation: 8 hours.
- **Stand-by:** 14 hours.

PAPER ROLL

Paper Type: Thermal paper
Width: 50mmX40mm

CONNECTIVITY

Interface: Serial/USB/Bluetooth

DRIVERS

SDK/ Windows driver / OPOS driver / Windows CE driver supported.

BATTERY CHARGER

Input: Voltage-AC 100-250/Current-1.0A (Max. at 110VA)

Output: Voltage-DC 8.4V/Current-0.8A

RELIABILITY

Printer unit: 35,000,000 lines

TPH: 120Km

Battery: 500 cycles rechargeable

DIMENSION

79.5x126.7x43.6mm

WEIGHT

293g incl. paper roll, battery

**YOUR RETAIL
AUTOMATION PARTNER**